



8 Inch Incandescent Look LED Green Arrow LED Traffic Signals





Features / Benefits

- High efficiency & long life LED light source
- Uniform non-pixelated illumination with "incandescent look"
- 90% reduction in power consumption vs. incandescent
- Easy to install with existing signal enclosure

Specifications

- Operating Voltage Range : 80 VAC to 135 VAC (120 VAC nominal)
- Operating Temperature Range : -40°C to +74°C
- Power Factor > 0.9
- Total Harmonic Distortion < 20%
- Turn on / Turn off time < 75 msec
- Meets FCC Title 47, Subpart B, Section 15 regulations for electrical noise
- Conforms to MIL-STD-810F for rain and blowing rain
- Conforms to MIL-STA-883, Test Method 1010, for temperature cycling requirements
- Conforms to MIL-STD-883, Test Method 2007, for mechanical vibration
- UV stabilized scratch resistant shell



Unit : mm(inch)

Distributed by **FORTTRAN** www.forttrantraffic.com
 Central Office: 1-800-387-4555
 Western Office: 604-502-9680

Model Number	Color	Dimension	Power Consumption (Watt) (Typ.)	Dominant Wavelength (nm) (Typ.)	Peak Minimum Maintained Luminous Intensity (cd) (min)
TRA-G08DD-N2	Green	200 mm	7.5	500	100



Address

1663 West 2nd Street, Pomona, CA 91766, U.S.A.
 Tel : 909-784-3333 Fax : 909-784-3330
 E-mail : Sales@eoius.com <http://www.eoius.com>

