




SmartSensor 8-conductor Cable

The SmartSensor™ 8-conductor cable can be used with the SmartSensor V, HD, and Advance retrofit to provide power and communication connectivity to the sensors. Heavy-duty and weather-resistant, this custom cable is ideal for cable runs from the sensor to the cabinet.

Features

- Two connectors available: 10-pin connector for connecting to SmartSensor V and HD; 26-pin connector for connecting to SmartSensor V retrofit, HD legacy, HD retrofit and Advance retrofit
- Provides power, RS-232, and RS-485 between sensor and cabinet
- Connector is keyed to ensure proper connection
- Color-coded for quick and easy wiring to terminal blocks, Click modules or other devices
- RS-485 and power conductors are twisted pairs; RS-232 conductors are lead wires
- Cable assembly is shielded with aluminum/mylar shield and a tinned copper drain wire
- RoHS compliant
- Cable end connector backshell is environmentally sealed, offering excellent immersion capability
- Connector backshell supports cable slack under extreme weather conditions





Technical Specifications

Cable

- RS-232 conductors: four lead wires
- RS-485 conductors: twisted pair
- RS-485 conductor nominal capacitance, conductor to conductor: less than 40 pF/ft at 1 kHz
- RS-232 and RS-485 conductor nominal conductor DC resistance: less than 16.7 ohms/1000 ft. (304.8 m) at 20°C
- Power conductors: twisted pair with nominal conductor DC resistance of less than 11.5 ohms/1000 ft. (304.8 m) at 20°C
- One tinned copper drain wire
- Cable assembly shielded with aluminum/polyester shield
- Jacket: 0.053-in. (1.3-mm) gray PVC
- Cable diameter: 0.41 in. (1.04 cm)
- Wire gauges:
 - Power wires: 20 AWG
 - Comms wires: 22 AWG
- RoHS compliant
- Approvals: UL/cUL Type CMG
- Ambient operating temperature: up to 221°F (105°C) dry / 167°F (75°C) wet
- Flammability rating: FT4
- UV resistant: yes (per UL 720 Hour Sunlight Resistance Test)

Connector

- Meets MIL-C-26482 specification
- 10 or 26 pins, depending on model
- Backshell is environmentally sealed
- Backshell offers excellent immersion capability
- All conductors that interface with the connector are encased in a single jacket
- Backshell has a strain relief with enough strength to support the cable slack under extreme weather conditions

Ordering Information

SmartSensor 8-conductor cable
 10-pin connector
SS-706-xxx – xxx indicates cable length

SmartSensor 8-conductor cable
 26-pin connector
SS-708-xxx – xxx indicates cable length

SmartSensor 8-conductor cable (bulk spool)
SS-707 – minimum 1000 ft. (304.8 m)

Wavetronix

78 East 1700 South
 Provo, UT 84606
 801.734.7200

sales@wavetronix.com
www.wavetronix.com